TECHNICAL DATA SHEET



Product code: 8211 Sector: Automotive Issue No: 1 Issue Date: 08/03/21

EE PERFORMANCE ENGINE OIL 10w50

Fully synthetic, full SAPS, for use in petrol and diesel engines.

Application

A performance engine oil featuring NANODRIVE low friction technology for vehicles requiring an A3/B4 or A3/B3 10w50 specification, predominantly for European and Asian extreme high performance vehicles.

Recommended for

ACEA A3/B4, ACEA A3/B3 API SN, SM, SL Abarth, Aston Martin, Ferrari, Fiat Maserati, Subaru, Volkswagen Audi Group inc. Seat, Skoda & Porsche Asian manufacturers

Typical Characteristics

Density @ 15°C, g/ml 0.860 Kinematic Viscosity @ 100°C, cSt. 19.5 Flashpoint, °C >200

Features & Benefits

- Increased engine power and torque from award winning NANODRIVE low friction technology and synthetic ester formulation.
- Extended component life and reduced operating temperatures as a result of the instant lubrication provided by NANODRIVE low friction technology.
- "Track day ready", high performance oil; delivers maximum engine performance whilst meeting manufacturer's specifications and recommended oil drain interval for on-road use.
- Full SAPS oil combined with NANODRIVE technology gives ultimate engine protection.
- Higher viscosity grade provides stable oil film and lubrication throughout full RPM range in arduous applications including track day use.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Footnotes: SAPS - Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer. Asian manufacturers - Including but not limited to Daihatsu, Honda, Hyundai, Infiniti, Kia, Lexus, Mazda, Mitsubishi, Nissan, Subaru, Suzuki and Toyota.







