

## TECHNICAL DATA SHEET



# SYNTHETIC SAE 10W-60 MOTOR OIL

## EUROPEAN FORMULA

PRODUCT # 10231, 10248, 10249, 10251,  
18023, 20231, 20248

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>33.65</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>0.862</b>
<b>Density @ 60°F, lb/gal</b>	<b>D-1298</b>	<b>7.19</b>
<b>CCS @ -25°C, CPS</b>	<b>D-5293</b>	<b>7,000 Max</b>
<b>MRV @ -30°C, CPS</b>	<b>D-4684</b>	<b>60,000 Max</b>
<b>Zinc, WT%</b>	<b>X-ray</b>	<b>0.085</b>
<b>TBN, Mg KOH/g</b>	<b>D-2896</b>	<b>7.5</b>
<b>Viscosity @ 40°C cSt</b>	<b>D-445</b>	<b>211</b>
<b>Viscosity @ 100°C cSt</b>	<b>D-445</b>	<b>25</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>149</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>425</b>
<b>Color</b>		<b>Light Brown</b>

**Lucas Synthetic SAE 10W-60 Motor Oil** is especially formulated for high mileage or high performance engines; it is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation.

**Lucas Synthetic SAE 10W-60 Motor Oil** is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.

**Lucas Synthetic SAE 10W-60 Motor Oil** is the perfect lubricant for high RPM and high temperature engines. The exclusive additive package in Lucas Synthetic SAE 10W-60 Motor Oil allows for extended drain intervals.

**Lucas Synthetic SAE 10W-60 Motor Oil** far exceeds all OEM specifications. Formulated to meet all motors that call for a Synthetic SAE 10W-60 motor oil.

**Meets the requirements of ACEA C2-16, C3-16, C2-12 and C3-12, API SN, VW50200, VW50500 and PSA Peugeot Citroën B712290.**