TECHNICAL DATA SHEET



Product Code: 7960 Sector: Motorsport Issue No: 2 Issue Date: 01/01/22

MOTORSPORT KR2T

Competition 2 Stroke Engine Oil

KR2T is a unique SAE 40 formulation,

Application

2-stroke oil with a high performance/low ash profile. Specifically developed for high revving 2 stroke engines. By mixing with petrol in the ratio recommended by the engine manufacturer, for use where maximum performance is required. (Typically, between 40:1 and 50:1 should give best results).

Performance Profile:

JASO FC API TC Global GC TISI

Typical Characteristics

Kinematic viscosity @ 100°C, cSt 13.7 Density @ 15°C, g/ml 0.885 Flashpoint °C >200

Features & Benefits

- Unique formulation improves sealing of the bores for increased power and torque.
- Burns cleanly for improved throttle response.
- Maximum lubricity for reduced wear.
- Prevents sticking throttle.
- Eliminates crank case deposits, making engine rebuilds easier.
- Suitable for all high performance air/water cooled 2 stroke engines.
- Can be used in outboard engines not requiring ashless oils.
- Dyed blue for easy confirmation fuel has been treated.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk
For H&S info or SDS, please visit our website:
www.millersoils.co.uk

