# **TECHNICAL DATA SHEET**



Product Code: 8123 Sector: Automotive (Passenger Car & LCV) Issue No: 3 Issue Date: 19/04/23

## TRIDENT PROFESSIONAL ENGINE OIL C2/C3 5w30

Fully synthetic, mid SAPS, for use in petrol, diesel and hybrid engines.

### **Application**

A professional engine oil suitable for the latest engine technology. Designed to meet OEM specifications. Recommended for engines requiring a C2 or C3 5w30 viscosity meeting the below manufacturer specifications.

#### **Performance Profile**

ACEA C2/C3 API SN, CF

#### Suitable for

BMW Longlife-04 Chrysler MS-11106 Fiat 9.55535-S3 GM dexos 2 GM-LL-B-025, GM-LL-A-025 MB 229.52, MB 229.51, MB 229.31 PSA B71-2290 <2014 Renault RN0700/ RN0710 VW 502 00 / 505 00 Asian manufacturers

#### **Features & Benefits**

- Excellent low temperature flow when cold starting, helping to instantly protect vital components.
- Viscosity stability at high temperatures, delivering reduced wear and tear on the engine and its components.
- Formulated with technology to provide engine cleanliness and durability which improves fuel economy, reduces emissions and provides extended drain capability.
- Utilising mid SAPS technology protecting particulate filters and controlling soot build up.
- Millers Oils stop start technology delivers instant protection under hot or cold conditions.

## **Typical Characteristics**

Density @ 15°C, g/ml 0.848 Kinematic Viscosity @ 100°C, cSt. 11.8 Flashpoint, °C >200

## **Technical & Health and Safety**

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Footnotes: SAPS - Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer







