# **TECHNICAL DATA SHEET**



Product code: 8366 Sector: Automotive (Passenger & LCV) Issue No: 3 Issue Date: 17/01/23

# **Driveline Flush 500ml**

A treatment to be added to oil in a driveline system before a drain & refill is to take place.

## **Description**

An oil based treatment designed to remove debris and contaminants in the gearbox and driveline system. Suitable for flushing manual gearboxes, automatic gearboxes (ATF systems), differentials, transfer cases & power steering systems.

#### **Application**

Applicable in both petrol and diesel passenger cars and light commercial vehicles (LCV) including hybrids.

### **Dosage Rate**

1 x 500 ml bottle treats: Up to 12 litres of driveline oil

#### **Directions for use**

Shake well before use.

Add full contents of the bottle to the oil in the gearbox, differential, transfer case or power steering system. Once added, drive the vehicle for at least 15 minutes then drain the oil and refill with fresh oil.

#### **Typical Characteristics**

Density @ 15°C, g/ml	0.880
Kinematic Viscosity @ 40°C, cSt	11.0
Flashpoint, °C	>140

#### **Features & Benefits**

- Driveline system will be clean and contaminant free
- Lower contaminant carry over from the previous fluid to the new fluid, which will enhance the protection from the fluid.
- Improves the efficiency of the driveline system, therefore increasing the fuel economy of the vehicle.
- An oil based treatment that is not aggressive to different materials and seal types, unlike solvent based flushing products.

# **Storage Instructions**

Store at ambient temperature. Avoid direct sunlight. Product efficacy within 24 months of date on bottle if stored according to the manufacturer's instructions.

#### **Technical & Health and Safety**

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Footnotes: Not suitable for Dual Clutch Transmission (DCT/DSG) or Continuously Variable Transmission (CVT) systems.







